



rio

DC Inverter-driven ductless split systems



High - efficiency (16 SEER) • Heat Pump systems • Compact & Quiet Design

www.greecooling.com



Features

- Inverter Technology
- Low Ambient Cooling - 5° F (208-230Volt systems)
- Low voltage start-up
- Intelligent Defrost
- Intelligent Pre-heating
- Comfortable Sleep Mode
- Auto Swing (Vertical)
- Multiple Fan Speeds
- Auto Clean
- Dry Anti-mildew design
- LED display
- Automatic Operation
- Self-diagnosis
- Memory Function
- Timer
- Control lock
- Fan Delay function



Model		GWH09KF-A3DNB1A *	GWH12KF-A3DNB1A	GWH09KF-D3DNB1C	GWH12KF-D3DNB1C	GWH18KG-D3DNB1C	GWH24KG-D3DNB1C
System Type		Heat Pump					
Power Supply		115V / 60Hz	115V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz
Rated Current Cooling	Amps	9	15	3.8	5.2	7.2	10.5
Rated Current Heating	Amps	9.5	15.5	3.4	4.7	10.7	12.8
System Performance							
Cooling Capacity (Min-Max)	Btu/h	9,000 (3,500-11,000)	11,800 (3,300-12,500)	9,000 (3,800-11,500)	12,000 (3,300-12,500)	18,000 (4,500-21,000)	22,000 (6,400-24,000)
Heating Capacity (Min-Max)	Btu/h	9,800 (2,500-11,000)	13,000 (3,400-13,500)	9,000 (3,400-13,500)	12,000 (3,400-12,500)	23,000 (4,000-23,000)	26,600 (4,100-26,600)
SEER/EER		16 / 12	16 / 9.4	16 / 10.6	16 / 10.3	16 / 11.1	16 / 10
HSPF		8.6	8.6	8.5	8.5	8.5	9.5
Indoor Unit							
Air Flow	CFM	330/277/224/188	341/288/235/200	330/277/224/188	341/288/235/200	471/400/330/271	589/471/412/353
Sound Pressure Level - T/H/M/L	db (A)	40/37/35/32	40/37/35/32	43/38/32/26	44/39/33/28	48/43/38/34	49/43/39/34
Unit Dimension (WxHxD)	inches	30.3 x 11.1 x 8	30.3 x 11.1 x 8	30.3 x 11.1 x 8	30.3 x 11.1 x 8	34 x 12 x 8.5	39.7 x 12.6 x 9.7
Package Dimension (WxHxD)	inches	33.3 x 14 x 11	33.3 x 14 x 11	33.3 x 14 x 11	33.3 x 14 x 11	37.3 x 15 x 11.2	42.4 x 15.7 x 12.9
Net / Gross Weight	lb	19 / 26	20 / 27	19 / 26	20 / 27	27 / 36	33 / 44
Outdoor Unit							
Compressor Type		DC Inverter-driven Twin rotary					
Sound Pressure Level	db (A)	53	55	49	52	56	56
Unit Dimension (WxHxD)	inches	33.4 x 21.3 x 12.6	33.3 x 23.2 x 12.6	28 x 21.6 x 12.5	28 x 21.6 x 12.5	37.6 x 27.6 x 15.6	37.6 x 27.6 x 15.6
Package Dimension (WxHxD)	inches	34.6 x 23.5 x 14.3	34.6 x 23.5 x 14.3	30.5 x 23.9 x 13.9	30.5 x 23.9 x 13.9	40.5 x 29.5 x 18	40.5 x 29.5 x 18
Net / Gross Weight	lb	75 / 84	75 / 84	64 / 73	69 / 78	117 / 106	112 / 123
Refrigerant / Charge	oz.	R410A / 37	R410A / 40.6	R410A / 26.1	R410A / 35.3	R410A / 45.9	R410A / 54.7
Line Set Size (Liquid - Suction)	inches	1/4" - 3/8"	1/4" - 3/8"	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"
Pre-Charge	Feet	25	25	25	25	25	25
Max. Line Run	Feet	50	50	50	50	82	82
Max. Elevation	Feet	33	33	33	33	33	33
MCA	Amps	17	18.2	10	10	15	15
MOCP	Amps	25	25	20	20	20	25

* Energy Star qualified model



On select models



Preserving resources remains our top priority, so we've printed this piece on recycled materials.



For more information, visit ACdoctor.com | greecooling.com